



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



## DATA SHEET

1/1

# TURPENTINE

**Slow solvent to dilute any kind of synthetic primer and enamels.**

## PRODUCT DATA

- *Specific gravity:* 0,860  $\pm$  0,05 g/cm<sup>3</sup> @ 20°C
- *Viscosity:* 12  $\pm$  2" CF4 at 20°C
- *Flash point:* 34°C

## PACKING

Available in 1, 5 and 25 lt cans.

## STORAGE

Up to 6 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.

The choice of the right solvent and its quantity makes the difference between a coating being suitable or not. There is no single solvent capable of thinning all the coatings currently used, but a wide range of solvents appropriate for each formulation.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.