



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

MORCAP

Water-based mineral acrylic coating, particularly suitable for waterproofing and decorating all sorts of interior and exterior surfaces. Permeable to water vapour, flexible, and with anti-carbonation properties.

PRODUCT DATA

- | | |
|--------------------------------|--|
| ➤ <i>Specific gravity:</i> | 2.000 ± 0.050 g/cm ³ @ 20°C |
| ➤ <i>Viscosity:</i> | Paste consistency. |
| ➤ <i>Finish:</i> | Depending on application. |
| ➤ <i>Air dry times (20°C):</i> | |
| <i>Dry to touch:</i> | 1 hour |
| ➤ <i>Recoat time:</i> | At least 6 hours air dry |

COVERAGE

2-3 m²/kg, depending on surface conditions.

PACKING

Available in 20 kg cans.

USES

Suitable for renewing, decorating, and waterproofing surfaces such as concrete, prefabricated units, one-coat mortars, plaster, cardboard plaster, and already painted surfaces on façades and interior surfaces, and as the final coat for thermal insulation systems.

SURFACES

Surfaces should be clean, hard, and free of easily breakable substances.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Telef. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/2

MORCAP

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a *spray gun or a trowel*. *In the latter case add 1 lt of water per container.*

Tools should be cleaned with water, and stains and splashes.

Do not apply at a temperature below 5°C and up to 30°C.

STORAGE

Up to 12 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous.