

# LANDECOLOR, S. A.

FABRICA: Polígono Industrial n.º 1













DATA SHEET 1/2

# **CONCENTRATED GENERAL-USE DYE**

Concentrated dye compatible with all kinds of water- and solvent-based paints. All shades are compatible among themselves allowing for an indefinite number of colours to be achieved.

### **PRODUCT DATA**

➤ Specific gravity: 1,030-1.070 g/cm³ @ 20°C

➤ Viscosity: 3 °CF4 at 20°C

Weathering resistance: HighCompatibility: Good

> Addition level: Below 8%

## **PACKING**

Available in 50 and 200 ml cans.

### **USES**

This product is designed to dye or adjust the colour of any kind of paint.

### SURFACE PREPARATION

Prepare the surface in the way required by the base paint.

# **COLOURS**

Black, red oxide, ocher, brown, lemon yellow, medium yellow, blue, red, green and violet.



# LANDECOLOR, S. A.

#### FABRICA: Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid) Fax ventas: 91 884 43 39 e-mail: landecolor@landecolor.com web: www.landecolor.es









PREMIO MED

**DATA SHEET** 2/2

### CONCENTRATED GENERAL-USE DYE

#### INSTRUCTIONS FOR USE

Please shake the container for the content to reach full homogeneity.

Mix with the base paint following the necessary ratio to obtain the shade of your choice.

Please be careful not to add too much dye.

Clean all utensils using water.

# **STORAGE**

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.

. . . . . . . . . . .

We quarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.