



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

ENVIRONMENTALLY FRIENDLY MATT POLITEX FAÇADES P-200

Copolymer-based, water-dispersed, weather-resistant plastic paint.

On 22 Nov. 2001, this product was the first to be awarded the Eco-Label in the Spanish Autonomous Region of Madrid. This award was again granted in 2009 according to DECISION 2007/457/EC.

APPROVED.

PRODUCT DATA

- | | |
|-------------------------|---------------------------------------|
| ➤ Specific gravity: | 1.730 + 0.05 g/cm ³ @ 20°C |
| ➤ Viscosity: | 120 + 5 KU at 20°C |
| ➤ Finish: | Matt. |
| ➤ Air dry times (20°C): | |
| Dry to touch: | 20 minutes |
| Totally dry: | 2 hours |
| ➤ Recoat time: | 4 hours |
| ➤ Washability test: | Class 2 (UNE 48243:2007). |

COVERAGE

5-6 m²/kg, depending on surface conditions.

PACKING

Available in 4, 8 and 15 ltr cans.

USES

This product is designed for protecting and decorating **façades, walls, cafeterias, flights of stairs, ceilings, business premises, etc.**

It is easy to apply, dries fast, features good washability properties and high resistance to weather.

It may be applied on **almost all everyday-use building materials**: render, mortar, concrete, isolating materials, fibre cement, blocks, prefabricated plaster pieces, etc.

Since this is a plastic paint, it is fire-resistant (M-1).



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/2

ENVIRONMENTALLY FRIENDLY MATT POLITEX FAÇADES P-200

SURFACES

Surfaces must be clean, in sound condition, and free of grease and easily breakable substances.

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a brush or a roller, apply a first coat thinned with 10% water, and 5% a second coat.

Tools must be cleaned with water.

COLOURS

White.

STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous.