



**LANDECOLOR, S. A.**

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



## DATA SHEET

1/2

### ROCATEX FOR PITTED AND DRIPPED FINISHES

Plastic paint especially designed for pitted and striped finishes. Provides great hardness and must be applied on firm surfaces.  
For interior and exterior use.

#### PRODUCT DATA

- *Specific gravity:* 1.600  $\pm$  0.050 g/cm<sup>3</sup> @ 20°C
- *Viscosity:* Paste consistency at 20°C
- *Finish:* Matt
- *Air dry times (20°C):*
  - Dry to touch:* 2-3 hours

#### COVERAGE

2-3 m<sup>2</sup>/kg, depending on surface conditions .

#### PACKING

Available in 15 ltr cans.

#### USES

Ease of application, high strength and abrasion resistance.

#### SURFACES

Surfaces must be clean, in sound condition, and free of grease and easily breakable substances.



**LANDECOLOR, S. A.**

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



## DATA SHEET

2/2

## ROCATEX FOR PITTED AND DRIPPED FINISHES

### INSTRUCTIONS FOR USE

Applied on hard surfaces or previously applied primer. Make the right consistency according to the job at hand.

Application by brush, roller spray gun and tirolesa.

Once the work has been finished, clean the tools with water.

### COLOURS

White.

### STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous.