



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

MULTIADHESIVE ACRIDIS

Solvent-based acrylic enamel especially designed for painting directly over galvanised metal sheets, aluminium, as well as iron and non-iron metals, and their light alloys. No priming required. Non-yellowing. Outstanding brightness and colour retention. Also provides appealing interior and exterior finishes.

PRODUCT DATA

- | | |
|-----------------------------|--|
| ➤ Specific gravity: | 1.380 + 0.150 g/cm ³ @ 20°C |
| ➤ Viscosity: | 100 + 5 KU at 20°C |
| ➤ Finish: | Gloss, satin and matt |
| ➤ Normal thickness of film: | From 25 to 30 microns |
| ➤ Air dry times (20°C): | |
| Dry to touch: | 40 minutes |
| Totally dry: | 4 hours |
| ➤ Recoat time: | At least 1 hour |
| ➤ Grinding Fineness: | 10-20 microns |

COVERAGE

10-11 m²/kg, depending on surface conditions and colors.

PACKING

Available in 0.750, 4 and 15 ltr cans.

USES

This is an excellent solution when it comes to painting on tough surfaces such as the ones mentioned above since it does not require prior priming. Due to its extreme hardness and high resistance to wear, this is an ideal product for coating **concrete** and on **solid brick**.

Easy to apply, great hardness and washability.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/2

MULTIADHESIVE ACRIDIS

SURFACES

The surfaces to be coated must be clean, consistent, and totally free of grease.

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a spray gun, brush or a roller:

Thin paint using our Fast Solvent for Synthetics or general-use nitro solvent until the adequate level of viscosity has been reached.

Tools must be cleaned with Slow Solvent for Synthetics or turpentine.

COLOURS

White and others.

STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.