



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

WHITE SATIN NITROCELLULOSE LACQUER

Nitrocellulose lacquer especially designed for the wood industry in general.

PRODUCT DATA

- *Specific gravity:* 1.290 + 0.05 g/cm³ @ 20°C
- *Viscosity:* 110 + 5 KU at 20°C
- *Finish:* Satin
- *Air dry times (20°C):*
 - Dry to touch:* 10-15 minutes
 - Dry without stickiness:* 15-20 minutes
 - Totally dry:* 1-2 hours
- *Recoat time:* At least 2 hours air dry

COVERAGE

5-6 m²/kg, depending on surface conditions.

PACKING

Available in 0.750 and 4 ltr cans.

USES

This product is suitable for any kind of ***lacquering project and for industrial uses in general.***

It may be used both indoors and outdoors. Its quick-drying properties make it particularly suitable for projects requiring fast handling of the pieces to be painted.

SURFACES

The surfaces to be coated must be clean, consistent, and totally free of grease.

If applied on unvarnished **wood**, please apply a first coat of our matt sealer or our nitro base primer and let it dry, sand it afterwards, and remove all remaining dust.

Please strip surfaces in a bad condition.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/2

WHITE SATIN NITROCELLULOSE LACQUER

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a spray gun, thinning paint using our general-use nitro solvent until the adequate level of viscosity has been reached (25-30" CF4).

Application conditions: Pressure: 3 to 4 atm.
Nozzle: 1 / 1.5 / 2 mm.

Tools must be cleaned with general-use nitro solvent.

COLOURS

White.

STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.