



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/3

QUICK-DRYING ANTI-CORROSION PRIMER FOR GENERAL USE

Anti-corrosion synthetic primer especially formulated for application on surfaces requiring quick drying due to the fast pace of the work performed. For general use.

PRODUCT DATA

- | | |
|-----------------------------|---------------------------------------|
| ➤ Specific gravity: | 1.600 ± 0.05 g/cm ³ @ 20°C |
| ➤ Viscosity: | 90 + 10 KU at 20°C |
| ➤ Finish: | semigloss and matt |
| ➤ Normal thickness of film: | 35 microns |
| ➤ Air dry times (20°C): | |
| Dry to touch: | 15 minutes |
| Dry without stickiness: | 20-30 minutes |
| Totally dry: | 30-60 minutes |
| ➤ Recoat time: | 24 hours |
| ➤ Grinding Fineness: | 30 microns |

MECHANICAL TESTS

- | | |
|-----------------------------|-----------------------|
| ➤ Erichsen cupping: | 7 mm |
| ➤ Adhesion: | 100% (cross-cut test) |
| ➤ Salt spray corrosion test | 100 hours |

COVERAGE

5-8 m²/kg, depending on surface conditions.

PACKING

Available in 4 and 15 ltr cans.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/3

QUICK-DRYING ANTI-CORROSION PRIMER FOR GENERAL USE

USES

Use as a **general-use** primer providing outstanding elasticity.

Its main features are its anti-rust power and the outstanding adhesion of enamels applied on this primer.

This product provides excellent water stability and outstanding hiding capacity.

The use of an **inadequate solvent** will create paint adhesion problems.

SURFACES

Surfaces must be clean, in sound condition, and free of grease and easily breakable substances.

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a spray gun, brush or a roller:

- **Spray gun:** Thin paint using our synthetic solvent until the adequate level of viscosity has been reached.

Application conditions:	Pressure:	3 to 4 atm.
	Nozzle:	1 / 1.5 / 2 mm.
	Coats:	one light coat.

- **Roller or brush:** Apply a first coat thinned with 10% synthetic solvent, and a second coat as supplied.

Tools must be cleaned with synthetic solvent.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

3/3

QUICK-DRYING ANTI-CORROSION PRIMER FOR GENERAL USE

COLOURS

Black matt, grey matt, red iron oxide matt, white matt, red satin, grey satin and black satin.

STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous