



# LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



## DATA SHEET

1/2

### ONE-COAT WHITE FALTECH

**High-performance special coating to be used on assembled false ceilings. This product helps to avoid problems caused by the use of plastic paint, as once it is dry, panels can be detached and handled without knocking some of the coating off.**

#### PRODUCT DATA

- *Specific gravity:* 1,550  $\pm$  0,050 g/cm<sup>3</sup> @ 20°C
- *Viscosity:* 95 + 5 KU at 20°C
- *Finish:* Matt.
- *Air dry times (20°C):*
  - Dry to touch:* 20 minutes
  - Totally dry:* 2 hours

#### COVERAGE

**3-4 m<sup>2</sup>/kg**, depending on surface conditions.

#### PACKING

Available in 20kg cans.

#### USES

Suitable for renewing false ceilings of industrial units, offices, large surfaces, etc., which cannot be detached to be painted.

#### SURFACES

The surfaces to be coated must be sanded, clean, consistent, and totally free of grease.



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



## DATA SHEET

2/2

# ONE-COAT WHITE FALTECH

## INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

The product may be applied using a **spray gun**

Atoxic.

Tools should be cleaned with water, and stains and splashes.

## STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.