



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

PEELABLE LACQUER VARNISH

Synthetic varnish especially formulated for protecting metals and light alloys which creates a plastic film to prevent rubbing and scratching. This paint is for general use whenever an appropriate anticorrosive protection is required. Easy to eliminate at any time.

PRODUCT DATA

- *Specific gravity:* 0,892 ± 0,05 g/cm³ @ 20°C
- *Viscosity:* 55 ± 5 KU at 20°C
- *Finish:* Semi-gloss
- *Air dry times (20°C):*
 - Dry to touch:* 10 minutes
 - Dry without stickiness:* 15-20 minutes
 - Totally dry:* 1 hour
- *Recoat time:* 1 hour

COVERAGE

8-10 m²/lt, depending on surface conditions.

PACKING

Available in 1, 4 and 15 ltr cans.

SURFACES

The surfaces to be coated must be sanded, clean, consistent, and totally free of grease.

INSTRUCTIONS FOR USE

Please stir the product before use for the content of the container to reach full homogeneity.

Apply a coat using a **brush, roller, or spray gun**. It should be thinned with our general-use nitro solvent.

Tools must be cleaned with general-use nitro solvent



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

2/2

PEELABLE LACQUER VARNISH

USES

Protection of machined parts, machines, axles, engines, etc. Protection of chromed objects during painting and land and sea transport operations.

Easy to apply, anti-rust and waterproofing.

The film of this paint can be easily torn out by hand, with no tools or solvents

needed. In order to facilitate this operation, thick layers of film must be applied.

After tearing out the paint, the surface looks absolutely clean, free of dust, grains, or waste.

COLOURS

Green and white.

STORAGE

Up to 24 months in original unopened container.

Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous.