



LANDECOLOR, S. A.

FABRICA : Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)

Fax ventas: 91 884 43 39

e-mail: landecolor@landecolor.com

web: www.landecolor.es



DATA SHEET

1/2

SMOOTH STONE-LIKE COATING

Water-proof hard coating providing great adhesion and enough elasticity to take in the expansions and contractions of the surfaces on which it has been applied. For interior and exterior use.

APPROVED.

PRODUCT DATA

- Specific gravity: 1,740 ± 0.05 g/cm³ @ 20°C
- Viscosity: 115 + 5 KU at 20°C
- Finish: Matt
- Air dry times (20°C):
 - Dry to touch: 2 hours
- Washability test: At least 1.000 cycles

COVERAGE

6-8 m²/kg, depending on surface conditions .

PACKING

Available in 15 ltr cans.

USES

This product is designed for decorating and coating **all kinds of buildings, especially outdoors**, such as façades, country estates, developments, industrial buildings, and sport facilities. It may also be applied indoors for innovative decorative uses.

SURFACES

This product provides great adhesion, which makes it ideal for application **on a large range of building materials**, i.e., render, mortar, concrete, natural and fake stone, bricks and other ceramic materials, fibre cement, and prefabricated plaster pieces. Surfaces must be clean, in sound condition, and free of easily breakable substances.



LANDECOLOR, S. A.

FABRICA: Polígono Industrial n.º 1

C/. Soria, 38 - Teléf. 91.884 33 59 - Fax 91.884 40 71 - 28864 AJALVIR (Madrid)
Fax ventas: 91 884 43 39
e-mail: landecolor@landecolor.com
web: www.landecolor.es



DATA SHEET

2/2

SMOOTH STONE-LIKE COATING

INSTRUCTIONS FOR USE

This product is supplied with the appropriate consistency to apply directly and no previous handling is required. It is only recommended to stir the content of the container once it has been opened for it to reach full homogeneity. The product may be applied using a **roller** or a **spray gun**. Do not apply in freezing temperatures, under the rain, or during peak sun exposure hours.

Once the work has been finished, clean the tools with water.

COLOURS

White and colour chard.

STORAGE

Up to 24 months in original unopened container.
Please keep away from freezing temperatures and direct exposure to sunlight.



We guarantee the quality of our products in accordance with our general conditions of sales and supply. Our technical recommendations of usage, expressed verbally, in written form, or by means of tests, are offered to the best of our knowledge and current experience. They constitute simple indications which do not intend any liability on our part nor do they exempt customers from their need to check by themselves that the products supplied by us match their required procedures and goals by conducting their own monitoring checks and tests.

The application and usage of these products are outside our control. Consequently, customers exclusively shall be liable for these. We accept no liability for any results other than the ones shown here. Our safety recommendations shall not prevent customers from determining their own amounts subject to the conditions of their premises. We reserve the right to change the data in this sheet without prior notice as data evolve technologically.

Issued on 30 Jun. 11. This DATA SHEET supersedes all previous.